

# Floor Console Heat Pump Ductless System

Indoor Model: **40MBFQ09---3**

## Submittal Data

Job Data:  Location:

Buyer:  Buyer P.O. #:  Carrier #:

Unit Number:  Model Number:

Performance Data Certified By:  Date:



### STANDARD FEATURES

- Modes: Cool, Heat, Dry, Fan, Auto
- Timer
- Auto-Restart
- Sleep mode
- Up-Down Louver control (fixed or swing)
- Air discharge from Top and/or bottom
- Follow Me (Sense Temperature at handheld remote)
- 46°F Heating Mode (Heating Setback)
- Aluminum Golden Hydrophilic pre-coated fins

### CONTROLS:

- Wireless Remote Controller included with indoor unit
- Optional Wired Remote Controller (Timer Function)
- Optional Wired Remote Controller KSACN0401AAA (7 Day programmable)

### LIMITED WARRANTY\*

- 10 year limited to original purchaser on compressor and parts upon timely registration, otherwise 5 years
- \*For residential applications. See warranty for full details.

System	Size	9	
	Indoor Model	40MBFQ09---3	
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208/230-1-60
	Power Supply	Indoor unit powered by outdoor unit	
	MCA	A.	0.29
Controls	Wireless Remote Controller (°F/°C Convertible)	Standard	
	Wired Remote Controller (°F/°C Convertible)	Optional	
Operating Range	Cooling Indoor DB Min -Max	°F(°C)	63~90 (17~32)
	Heating Indoor DB Min -Max	°F(°C)	32~86 (0~30)
Piping	Pipe Connection Size - Liquid	in (mm)	1/4 (6.35)
	Pipe Connection Size - Suction	in (mm)	3/8 (9.52)

Indoor Coil	Face Area	Sq. Ft.	2.1
	No. Rows	2	
	Fins per inch	19	
	Circuits	2	
Indoor	Unit Width	in (mm)	27.56 (700)
	Unit Height	in (mm)	23.62 (600)
	Unit Depth	in (mm)	8.27 (210)
	Net Weight	lbs (kg)	32.41 (14.7)
	Number of Fan Speeds	3	
	Airflow (lowest to highest)	CFM	220/250/280
	Sound Pressure (lowest to highest)	dB(A)	37/38/41
	Air throw Data	ft (m)	23 (7)
Field Drain Pipe Size O.D.	in (mm)	1 (25.4)	

For Compatibility See Product Data

Performance may vary based on the outdoor unit matched to. See compatible outdoor units pages for Performance Data.

# Accessories

53DS-900---118	Condensate Pump (208/230V)
KSACN0101AAA	Wired Remote Control with Timer Function
KSACN0401AAA	Wired Remote Control 7 day Programmable
KSAIC0101230	24V Interface Kit 208/230V
53DS-900---089	Insulated 25' Line Set - 1/4" x 3/8"
53DS-900---090	Wireless Remote Control Locking Mount Kit

## Construction View

Indoor Model: 40MBFQ09---3

