

Floor Console Heat Pump Ductless System

Indoor Model: **40MBFQ24---3**

Submittal Data

Job Data: Location:

Buyer: Buyer P.O. #: Carrier #:

Unit Number: Model Number:

Performance Data Certified By: Date:



STANDARD FEATURES

- Modes: Cool, Heat, Dry, Fan, Auto
- Timer
- Auto-Restart
- Sleep mode
- Up-Down Louver control (fixed or swing)
- Capable to be mounted on Floor and Ceiling**
- Follow Me (Sense Temperature at handheld remote)
- 46°F Heating Mode (Heating Setback)
- Aluminum Golden Hydrophilic pre-coated fins

CONTROLS:

- Wireless Remote Controller included with indoor unit
- Optional Wired Remote Controller (Timer Function)
- Optional Wired Remote Controller KSACN0501AAA (7 Day programmable)

LIMITED WARRANTY*

- 10 year limited to original purchaser on compressor and parts upon timely registration, otherwise 5 years
- *For residential applications. See warranty for full details.

System	Size	24	
	Indoor Model	40MBFQ24---3	
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208/230-1-60
	Power Supply	Indoor unit powered by outdoor unit	
	MCA	A.	1
Controls	Wireless Remote Controller (°F/°C Convertible)	Standard	
	Wired Remote Controller (°F/°C Convertible)	Optional	
Operating Range	Cooling Indoor DB Min -Max	°F(°C)	63~90 (17~32)
	Heating Indoor DB Min -Max	°F(°C)	32~86 (0~30)
Piping	Pipe Connection Size - Liquid	in (mm)	3/8 (9.52)
	Pipe Connection Size - Suction	in (mm)	5/8 (16)

Indoor Coil	Face Area	Sq. Ft.	2.5
	No. Rows	3	
	Fins per inch	19	
	Circuits	7	
Indoor	Unit Width	in (mm)	42.05(1068)
	Unit Height	in (mm)	26.57(675)
	Unit Depth	in (mm)	9.25(235)
	Net Weight	lbs (kg)	58.42(26.5)
	Number of Fan Speeds	3	
	Airflow (lowest to highest)	CFM	600/710/760
	Sound Pressure (lowest to highest)	dB(A)	46/50/52
	Air throw Data	ft (m)	26 (8)
Field Drain Pipe Size O.D.	in (mm)	1 (25.4)	

For Compatibility See Product Data

Performance may vary based on the outdoor unit matched to. See compatible outdoor units pages for Performance Data.

Accessories

53DS-900---118	Condensate Pump (208/230V)
KSACN0101AAA	Wired Remote Control with Timer Function
KSACN0501AAA	Wired Remote Control 7 day Programmable
KSAIF0401AAA	Wi-Fi™ Kit Console
KSAIC0101230	24V Interface Kit 208/230V
53DS-900---090	Wireless Remote Control Locking Mount Kit

Construction View

Indoor Model: 40MBFQ24---3

