

# Floor Console Heat Pump Ductless System

Indoor Model: **40MBFQ36---3**

## Submittal Data

Job Data:  Location:

Buyer:  Buyer P.O. #:  Carrier #:

Unit Number:  Model Number:

Performance Data Certified By:  Date:



### STANDARD FEATURES

Modes: Cool, Heat, Dry, Fan, Auto  
 Timer  
 Auto-Restart  
 Sleep mode  
 Up-Down Louver control (fixed or swing)  
**Capable to be mounted on Floor and Ceiling**  
 Follow Me (Sense Temperature at handheld remote)  
 46°F Heating Mode (Heating Setback)  
 Aluminum Golden Hydrophilic pre-coated fins

### CONTROLS:

Wireless Remote Controller included with indoor unit  
 Optional Wired Remote Controller (Timer Function)  
 Optional Wired Remote Controller KSACN0501AAA (7 Day programmable)

### LIMITED WARRANTY\*

- 10 year limited to original purchaser on compressor and parts upon timely registration, otherwise 5 years
- \*For residential applications. See warranty for full details.

System	Size	36	
	Indoor Model	40MBFQ36---3	
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208/230-1-60
	Power Supply	Indoor unit powered by outdoor unit	
	MCA	A.	1.23
Controls	Wireless Remote Controller (°F/°C Convertible)	Standard	
	Wired Remote Controller (°F/°C Convertible)	Standard	
Operating Range	Cooling Indoor DB Min -Max	°F(°C)	63~90 (17~32)
	Heating Indoor DB Min -Max	°F(°C)	32~86 (0~30)
Piping	Pipe Connection Size - Liquid	in (mm)	3/8 (9.52)
	Pipe Connection Size - Suction	in (mm)	5/8 (16)

Indoor Coil	Face Area	Sq. Ft.	3.2
	No. Rows	3	
	Fins per inch	19	
	Circuits	9	
Indoor	Unit Width	in (mm)	50.59 (1285)
	Unit Height	in (mm)	9.25 (235)
	Unit Depth	in (mm)	26.57 (675)
	Net Weight	lbs (kg)	69 (31.3)
	Number of Fan Speeds	3	
	Airflow (lowest to highest)	CFM	638/917/1037
	Sound Pressure (lowest to highest)	dB(A)	43/49/54
	Air throw Data	ft (m)	33(10)
Field Drain Pipe Size O.D.	in (mm)	1 (25.4)	

For Compatibility See Product Data

Performance may vary based on the outdoor unit matched to. See compatible outdoor units pages for Performance Data.

# Accessories

53DS-900---118	Condensate Pump (208/230V)
KSACN0101AAA	Wired Remote Control with Timer Function
KSACN0501AAA	Wired Remote Control 7 day Programmable
KSAIF0401AAA	Wi-Fi™ Kit Console
KSAIC0101230	24V Interface Kit 208/230V
53DS-900---090	Wireless Remote Control Locking Mount Kit

## Construction View

Indoor Model: 40MBFQ36---3

