

# Floor Console Heat Pump Ductless System

Indoor Model: **40MBFQ58---3**

## Submittal Data

Job Data:  Location:

Buyer:  Buyer P.O. #:  Carrier #:

Unit Number:  Model Number:

Performance Data Certified By:  Date:



### STANDARD FEATURES

- Modes: Cool, Heat, Dry, Fan, Auto
- Timer
- Auto-Restart
- Sleep mode
- Up-Down Louver control (fixed or swing)
- Capable to be mounted on Floor and Ceiling**
- Follow Me (Sense Temperature at handheld remote)
- 46°F Heating Mode (Heating Setback)
- Anti-corrosive fin coating

### CONTROLS:

- Wireless Remote Controller included with indoor unit
- Optional Wired Remote Controller (Timer Function)
- Optional Wired Remote Controller KSACN0501AAA (7 Day programmable)

### LIMITED WARRANTY\*

- 10 year limited to original purchaser on compressor and parts upon timely registration, otherwise 5 years
- \*For residential applications. See warranty for full details.

System	Size		58
	Indoor Model		40MBFQ58---3
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208/230-1-60
	Power Supply Indoor unit powered by outdoor unit		
	MCA	A.	1.48
Controls	Wireless Remote Controller (°F/°C Convertible)		Standard
	Wired Remote Controller (°F/°C Convertible)		Standard
Operating Range	Cooling Indoor DB Min -Max	°F(°C)	63~90 (17~32)
	Heating Indoor DB Min -Max	°F(°C)	32~86 (0~30)
Piping	Pipe Connection Size - Liquid	in (mm)	3/8 (9.52)
	Pipe Connection Size - Suction	in (mm)	3/4 (19)

Indoor Coil	Face Area	Sq. Ft.	8.1
	No. Rows		4
	Fins per inch		19
	Circuits		12
Indoor	Unit Width	in (mm)	64.96 (1650)
	Unit Height	in (mm)	9.25 (235)
	Unit Depth	in (mm)	26.57 (675)
	Net Weight	lbs (kg)	110 (50)
	Number of Fan Speeds		3
	Airflow (lowest to highest)	CFM	796/1029/1385
	Sound Pressure (lowest to highest)	dB(A)	46/49/55
	Air throw Data	ft (m)	39(12)
Field Drain Pipe Size O.D.	in (mm)	1 (25.4)	

For Compatibility See Product Data

Performance may vary based on the outdoor unit matched to. See compatible outdoor units pages for Performance Data.

# Accessories

53DS-900---118	Condensate Pump (208/230V)
KSACN0101AAA	Wired Remote Control with Timer Function
KSACN0501AAA	Wired Remote Control 7 day Programmable
KSAIF0401AAA	Wi-Fi™ Kit Console
KSAIC0101230	24V Interface Kit 208/230V
53DS-900---090	Wireless Remote Control Locking Mount Kit

## Construction View

Indoor Model: 40MBFQ58---3

