

# High Wall Cooling Only Ductless System

Indoor Model: **40MHHC09---3**

## Submittal Data

Job Data:  Location:

Buyer:  Buyer P.O. #:  Carrier #:

Unit Number:  Model Number:

Performance Data Certified By:  Date:



### STANDARD FEATURES

- Up-Down Louver control (fixed or swing)
- Remove filter from the top
- Improved serviceability with easy access to fan and electrical connections
- Four fan speeds
- Sleep Mode
- Follow Me (senses temperature at handheld remote)
- Quiet operation
- Anti-corrosive fin coating

### Controls:

- Wireless Remote Controller included with indoor unit
- Optional Wired Remote Controller KSACN0401AAA

### LIMITED WARRANTY\*

- 10 year limited to original purchaser on compressor and parts upon timely registration, otherwise 5 years

\*For residential applications. See warranty for full details.

System	Size	9	
	Indoor Model	40MHHC09---3	
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208/230-1-60
	Power Supply	Powered from outdoor unit	
	MCA	A.	0.25
Controls	Wireless Remote Controller (°F/°C Convertible)	Standard	
	Wired Remote Controller (°F/°C Convertible)	Optional	
Operating Range	Cooling Indoor DB Min -Max	° F (° C)	63~90 (17~32)
	Pipe Connection Size - Liquid	in (mm)	1/4 (6.35)
Piping	Pipe Connection Size - Suction	in (mm)	3/8 (9.52)

Indoor Coil	Face Area (sq. ft.)	Sq. Ft.	1.14
	No. Rows	2	
	Fins per inch	20	
	Circuits	2	
Indoor	Unit Width	in (mm)	28.53 (725)
	Unit Height	in (mm)	11.81 (300)
	Unit Depth	in (mm)	7.75 (197)
	Net Weight	lbs (kg)	16.53 (7.5)
	Number of Fan Speeds	4	
	Airflow (lowest to highest)	CFM	177/224/260/286
	Sound Pressure (lowest to highest)	dB(A)	28/35/39/40
	Air throw Data	ft (m)	20.3 (6.2)
	Moisture removal	Pint/h (L/h)	2.07 (0.98)
Field Drain Pipe Size O.D.	in (mm)	0.625 (16)	

Performance may vary based on the outdoor unit matched to. See compatible outdoor units pages for Performance Data.

### Accessories

53DS-900---118	Condensate Pump (208/230V)
KSACN0401AAA	Wired Remote Control 7 Day Programmable
53DS-900---089	Insulated 25' Line Set - 1/4" x 3/8"

## Compatibility Table

Indoor Unit	40MHHC09---3
Outdoor Unit	38MHRC09A--3

## Construction View

Indoor Model: **40MHHC09---3**

