

High Wall Cooling Only Ductless System

Indoor Model: **40MHHC12---1**

Submittal Data

Job Data: Location:

Buyer: Buyer P.O. #: Carrier #:

Unit Number: Model Number:

Performance Data Certified By: Date:



STANDARD FEATURES

- Up-Down Louver control (fixed or swing)
- Remove filter from the top
- Improved serviceability with easy access to fan and electrical connections
- Four fan speeds
- Sleep Mode
- Follow Me (senses temperature at handheld remote)
- Quiet operation
- Aluminum Blue Hydrophilic pre-coated fins

Controls:

- Wireless Remote Controller included with indoor unit
- Optional Wired Remote Controller KSACN0401AAA

LIMITED WARRANTY*

- 10 year limited to original purchaser on compressor and parts upon timely registration, otherwise 5 years

*For residential applications. See warranty for full details.

| | | | |
|-----------------|--|-------------------------------|---------------|
| System | Size | 12 | |
| | Indoor Model | 40MHHC12---1 | |
| Electrical | Voltage, Phase, Cycle | V/Ph/Hz | 115-1-60 |
| | Power Supply | Powered from outdoor unit | |
| | MCA | A. | 0.3 |
| Controls | Wireless Remote Controller (°F/°C Convertible) | Standard | |
| | Wired Remote Controller (°F/°C Convertible) | Optional | |
| Operating Range | Cooling Indoor DB Min -Max | ° F (° C) | 63~90 (17~32) |
| | Piping | Pipe Connection Size - Liquid | in (mm) |
| Piping | Pipe Connection Size - Suction | in (mm) | 1/2 (12.7) |

| | | | |
|----------------------------|------------------------------------|--------------|-----------------|
| Indoor Coil | Face Area (sq. ft.) | Sq. Ft. | 1.48 |
| | No. Rows | 2 | |
| | Fins per inch | 20 | |
| | Circuits | 2 | |
| Indoor | Unit Width | in (mm) | 32.00 (813) |
| | Unit Height | in (mm) | 11.81 (300) |
| | Unit Depth | in (mm) | 7.75 (197) |
| | Net Weight | lbs (kg) | 17.64 (8) |
| | Number of Fan Speeds | 4 | |
| | Airflow (lowest to highest) | CFM | 190/239/301/328 |
| | Sound Pressure (lowest to highest) | dB(A) | 29/36/41/42 |
| | Air throw Data | ft (m) | 22 (6.7) |
| | Moisture removal | Pint/h (L/h) | 3.17 (1.50) |
| Field Drain Pipe Size O.D. | in (mm) | 0.625 (16) | |

Performance may vary based on the outdoor unit matched to. See compatible outdoor units pages for Performance Data.

Accessories

| | |
|----------------|---|
| 53DS-900---117 | Condensate Pump (115v) |
| KSACN0401AAA | Wired Remote Control 7 Day Programmable |
| 53DS-900---008 | Insulated 25' Line Set - 1/4" x 1/2" |

Compatibility Table

| | |
|--------------|--------------|
| Indoor Unit | 40MHHC12---1 |
| Outdoor Unit | 38MHRC12A--1 |

Construction View

Indoor Model: 40MHHC12---1

