

High Wall Heat Pump Ductless System

Indoor Model: **40MHHQ09---3**

Submittal Data

Job Data: Location:

Buyer: Buyer P.O. #: Carrier #:

Unit Number: Model Number:

Performance Data Certified By: Date:



STANDARD FEATURES

- Up-Down Louver control (fixed or swing)
- Remove filter from the top
- Improved serviceability with easy access to fan and electrical connections
- Four fan speeds
- Sleep Mode
- Follow Me (senses temperature at handheld remote)
- Quiet operation
- Aluminum Blue Hydrophilic pre-coated fins

Controls:

- Wireless Remote Controller included with indoor unit
- Optional Wired Remote Controller KSACN0401AAA

LIMITED WARRANTY*

- 10 year limited to original purchaser on compressor and parts upon timely registration, otherwise 5 years

*For residential applications. See warranty for full details.

| | | | |
|-----------------|--|---------------------------|---------------|
| System | Size | 9 | |
| | Indoor Model | 40MHHQ09---3 | |
| Electrical | Voltage, Phase, Cycle | V/Ph/Hz | 208/230-1-60 |
| | Power Supply | Powered from outdoor unit | |
| | MCA - Rated Current | A. | 0.22 |
| Controls | Wireless Remote Controller (°F/°C Convertible) | Standard | |
| | Wired Remote Controller (°F/°C Convertible) | Optional | |
| Operating Range | Cooling Indoor DB Min -Max | ° F (° C) | 62~90 (17~32) |
| | Heating Indoor DB Min -Max | ° F (° C) | 32~86 (0~30) |
| Piping | Pipe Connection Size - Liquid | in (mm) | 1/4 (6.35) |
| | Pipe Connection Size - Suction | in (mm) | 3/8 (9.52) |

| | | | |
|----------------------------|------------------------------------|--------------|-----------------|
| Indoor Coil | Face Area (sq. ft.) | Sq. Ft. | 1.5 |
| | No. Rows | 2 | |
| | Fins per inch | 21 | |
| | Circuits | 2 | |
| Indoor | Unit Width | in (mm) | 28.53 (725) |
| | Unit Height | in (mm) | 11.81 (300) |
| | Unit Depth | in (mm) | 7.75 (197) |
| | Net Weight | lbs (kg) | 17.64 (8.0) |
| | Number of Fan Speeds | 4 | |
| | Airflow (lowest to highest) | CFM | 153/253/282/324 |
| | Sound Pressure (lowest to highest) | dB(A) | 30/37/41/43 |
| | Air throw Data | ft (m) | 20.3 (6.2) |
| | Moisture removal | Pint/h (L/h) | 2.37 (1.12) |
| Field Drain Pipe Size O.D. | in (mm) | 0.625 (16) | |

Performance may vary based on the outdoor unit matched to. See compatible outdoor units pages for Performance Data.

Accessories

| | |
|----------------|---|
| 53DS-900---118 | Condensate Pump (208/230V) |
| KSACN0401AAA | Wired Remote Control 7 Day Programmable |
| 53DS-900---089 | Insulated 25' Line Set - 1/4" x 3/8" |

Construction View

