

High Wall Heat Pump Ductless System

Indoor Model: **40MHHQ24---3**

Submittal Data

Job Data: Location:

Buyer: Buyer P.O. #: Carrier #:

Unit Number: Model Number:

Performance Data Certified By: Date:



STANDARD FEATURES

- Up-Down Louver control (fixed or swing)
- Remove filter from the top
- Improved serviceability with easy access to fan and electrical connections
- Four fan speeds
- Sleep Mode
- Follow Me (senses temperature at handheld remote)
- Quiet operation
- Anti-corrosive fin coating

Controls:

- Wireless Remote Controller included with indoor unit
- Optional Wired Remote Controller KSACN0401AAA

LIMITED WARRANTY*

- 10 year limited to original purchaser on compressor and parts upon timely registration, otherwise 5 years

*For residential applications. See warranty for full details.

| | | | |
|-----------------|--|---------------------------|---------------|
| System | Size | 24 | |
| | Indoor Model | 40MHHQ24---3 | |
| Electrical | Voltage, Phase, Cycle | V/Ph/Hz | 208/230-1-60 |
| | Power Supply | Powered from outdoor unit | |
| | MCA | A. | 0.45 |
| Controls | Wireless Remote Controller (°F/°C Convertible) | Standard | |
| | Wired Remote Controller (°F/°C Convertible) | Optional | |
| Operating Range | Cooling Indoor DB Min -Max | ° F (° C) | 63~90 (17~32) |
| | Heating Indoor DB Min -Max | ° F (° C) | 32~86 (0~30) |
| Piping | Pipe Connection Size - Liquid | in (mm) | 3/8 (9.52) |
| | Pipe Connection Size - Suction | in (mm) | 5/8 (16) |

| | | | |
|----------------------------|------------------------------------|--------------|-----------------|
| Indoor Coil | Face Area (sq. ft.) | Sq. Ft. | 2.58 |
| | No. Rows | 2 | |
| | Fins per inch | 20 | |
| | Circuits | 2 | |
| Indoor | Unit Width | in (mm) | 43.83 (1113) |
| | Unit Height | in (mm) | 13.41 (341) |
| | Unit Depth | in (mm) | 9.22 (234) |
| | Net Weight | lbs (kg) | 40.12(18.2) |
| | Number of Fan Speeds | 4 | |
| | Airflow (lowest to highest) | CFM | 353/483/589/647 |
| | Sound Pressure (lowest to highest) | dB(A) | 38/42/48/49 |
| | Air throw Data | ft (m) | 37.7 (11.5) |
| | Moisture removal | Pint/h (L/h) | 5.73 (2.71) |
| Field Drain Pipe Size O.D. | in (mm) | 0.625 (16) | |

Performance may vary based on the outdoor unit matched to. See compatible outdoor units pages for Performance Data.

Accessories

| | |
|----------------|---|
| 53DS-900---118 | Condensate Pump (208/230V) |
| KSACN0401AAA | Wired Remote Control 7 Day Programmable |

Compatibility Table

| | |
|--------------|--------------|
| Indoor Unit | 40MHHQ24---3 |
| Outdoor Unit | 38MHRQ24A--3 |

Construction View

Indoor Model: 40MHHQ24---3

