

High Wall Heat Pump Ductless System



Indoor Model: **619PHAQ18XA3**

Submittal Data

Job Data: Location:

Buyer: Buyer P.O. #: Carrier #:

Unit Number: Model Number:

Performance Data Certified By: Date:



STANDARD FEATURES

- Modes: Cool, Heat, Smart Dry, Fan, Auto
- Turbo Mode
- Fully Modulating fan speeds
- Sleep Mode
- Up-Down / Right-Left Louver control (fixed or swing)
- Built-in Relative Humidity Sensor
- ECO Mode
- Carbon Filter
- Follow Me (senses temperature at handheld remote)
- Heating Setback (46°F Heating Mode)
- Aluminum Golden Hydrophilic pre-coated fins

Controls:

- Wi-Fi Kit included with indoor unit
- Wireless Remote Controller included with indoor unit
- Wired Remote Controller KSACN0401AAA (7 Day programmable) (Optional)

LIMITED WARRANTY*

- 10 year limited to original purchaser on compressor and parts upon timely registration, otherwise 5 years
- *For residential applications. See warranty for full details.

System	Size	18	
	Indoor Model	619PHAQ18XA3	
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208/230-1-60
	Power Supply	208/230-1-60	
	MCA	A.	0.5
Controls	Wireless Remote Controller (°F/°C Convertible)	Standard	
	Wired Remote Controller (°F/°C Convertible)	Optional	
Operating Range	Cooling Indoor DB Min -Max	° F (° C)	62~90 (17~32)
	Heating Indoor DB Min -Max	° F (° C)	32~86 (0~30)
Piping	Pipe Connection Size - Liquid	in (mm)	3/8" (9.52)
	Pipe Connection Size - Suction	in (mm)	5/8" (15.9)

Indoor Coil	Face Area (sq. ft.)	Sq. Ft.	3.9	
	No. Rows	3		
	Fins per inch	21		
	Circuits	7		
Indoor	Unit Width	in (mm)	49.57 (1259)	
	Unit Height	in (mm)	14.25 (362)	
	Unit Depth	in (mm)	11.10 (282)	
	Net Weight	lbs (kg)	43.4(19.7)	
	Number of Fan Speeds		4	
	Airflow (lowest to highest)	CFM	261/389/528/926	
	Sound Pressure (lowest to highest)	dB(A)	35.1/40.8/46.1/55.9	
	Air throw Data	ft (m)	28.80 (8.7)	
	Moisture removal	Pint/h (L/h)	3.8 (1.8)	
	Field Drain Pipe Size O.D.	in (mm)	1 (25.4)	

Performance may vary based on the outdoor unit matched to. See compatible outdoor units pages for Performance Data.
For Compatibility See Product Data

Accessories

53DS-900---118	Condensate Pump
KSACN0401AAA	Wired Remote Control 7 Day Programmable
KSAIC0101230 or KSAIC0301230	24V Interface Kit 230V

Construction View

